

The enumerate package*

David Carlisle

2023/07/04

This file is maintained by the L^AT_EX Project team.
Bug reports can be opened (category tools) at
<https://latex-project.org/bugs.html>.

This package is retained in the L^AT_EX tools bundle for stability reasons. Whilst bug fixes will be applied to `enumerate`, no *new* features will be considered. For new material, the L^AT_EX team recommends that `enumitem` is used in place of `enumerate`.

Abstract

This package gives the `enumerate` environment an optional argument which determines the style in which the counter is printed.

An occurrence of one of the tokens `A a I i 1` produces the value of the counter printed with (respectively) `\Alph \alph \Roman \roman` or `\arabic`.

These letters may be surrounded by any strings involving any other T_EX expressions, however the tokens `A a I i 1` must be inside a `{ }` group if they are not to be taken as special.

1 Examples

| | |
|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EX i. one one one one one one one one one one one one one | <pre>\begin{enumerate}[EX i.] \item one one one one one one one one one one one\label{LA} \item two \begin{enumerate}[\{example} a)] \item one of two one of two one of two\label{LB} \item two of two \end{enumerate} \end{enumerate}</pre> |
| EX ii. two | |
| example a) one of two one of two one of two | |
| example b) two of two | |
| A-1 one | <pre>\begin{enumerate}[\{A}-1] \item one\label{LC} \item two \end{enumerate}</pre> |
| A-2 two | |

*This file has version number v3.00, last revised 2023/07/04.

`\label` and `\ref` may be used as with the standard `enumerate` environment. `\ref` only produces the counter value, not the whole label. `\ref` prints the value in the same style as `\item`, as determined by the presence of one of the tokens `A a I i 1` in the optional argument. In the above example `\ref{LA}`, `\ref{LB}` and `\ref{LC}` produce ‘i’, ‘ia’ and ‘1’ respectively.

2 Macros

```
1 (*package)
```

`\@enlab` Internal token register used to build up the label command from the optional argument.

```
2 \newtoks\@enLab
```

`\@enQmark` This just expands to a ‘?’. `\ref` will produce this, if no counter is printed.

```
3 \def\@enQmark{?}
```

The next four macros build up the command that will print the item label. They each gobble one token or group from the optional argument, and add corresponding tokens to the register `\@enLab`. They each end with a call to `\@enloop`, which starts the processing of the next token.

`\@enLabel` Add the counter to the label. #2 will be one of the ‘special’ tokens `A a I i 1`, and is thrown away. #1 will be a command like `\Roman`.

```
4 \def\@enLabel#1#2{%
5   \edef\@enthe{\noexpand#1{\@enumctr}}%
6   \@enLab\expandafter{\the\@enLab\csname the\@enumctr\endcsname}%
7   \@enloop}
```

`\@enSpace` Add a space to the label. The tricky bit is to gobble the space token, as you can `\@enSpace` not do this with a macro argument.

```
8 \def\@enSpace{\afterassignment\@enSpace\let\@tempa= }
9 \def\@enSpace{\@enLab\expandafter{\the\@enLab\space}\@enloop}
```

`\@enGroup` Add a `{ }` group to the label.

```
10 \def\@enGroup#1{\@enLab\expandafter{\the\@enLab{#1}}\@enloop}
```

`\@enOther` Add anything else to the label

```
11 \def\@enOther#1{\@enLab\expandafter{\the\@enLab#1}\@enloop}
```

`\@enloop` The body of the main loop. Eating tokens this way instead of using `\@tfor` lets you see spaces and **all** braces. `\@tfor` would treat `a` and `{a}` as special, but not `{{a}}`.

```
12 \def\@enloop{\futurelet\@entemp\@enloop@}
13 \def\@enloop@{%
14   \ifx A\@entemp           \def\@tempa{\@enLabel\Alph } \else
15   \ifx a\@entemp           \def\@tempa{\@enLabel\alph } \else
16   \ifx i\@entemp           \def\@tempa{\@enLabel\roman } \else
17   \ifx I\@entemp           \def\@tempa{\@enLabel\Roman } \else
18   \ifx 1\@entemp           \def\@tempa{\@enLabel\arabic} \else
19   \ifx \@sptoken\@entemp   \let\@tempa\@enSpace       \else
```

```

20 \ifx \bgroup\@entemp \let\@tempa\@enGroup \else
21 \ifx \@enum@\@entemp \let\@tempa\@gobble \else
22 \let\@tempa\@enOther
Hook for possible extensions
23 \enhook
24 \fi\fi\fi\fi\fi\fi\fi\fi
Process the current token, then look at the next.
25 \@tempa}

```

`\@enhook` Hook for possible extensions. Some packages may want to extend the number of special characters that are associated with counter representations. This feature was requested to enable Russian alphabetic counting, but here I give an example of a footnote symbol counter, triggered by `*`.

To enable a new counter type based on a letter, you just need to add a new `\ifx` clause by analogy with the code above. So for example to make `*` trigger footnote symbol counting, a package should do the following.

Initialise the hook, in case the package is loaded before `enumerate`.

```
\providecommand\@enhook{}
```

Add to the hook a new `\ifx` clause that associates `*` with the `\fnsymbol` counter command.

```

\g@addto@macro\@enhook{%
  \ifx *\@entemp
    \def\@tempa{\@enLabel\fnsymbol}%
  \fi}

```

This code sequence should work whether it is loaded before or after this `enumerate` package. Any number of new counter types may be added in this way.

At this point we just need initialise the hook, taking care not to overwrite any definitions another package may already have added.

```
26 \providecommand\@enhook{}
```

`\enumerate` The new `enumerate` environment. This is the first half of the original `enumerate` environment. If there is an optional argument, call `\@@enum@` to define the label commands, otherwise call `\@enum@` which is the second half of the original definition.

```

27 \def\enumerate{%
28 \ifnum \@enumdepth >3 \@toodeep\else
29 \advance\@enumdepth \@ne
30 \edef\@enumctr{enum\romannumeral\the\@enumdepth}\fi
31 \@ifnextchar [{\@@enum@}{\@enum@}]

```

`\@@enum@` Handle the optional argument.

```
32 \def\@@enum#[#1]{%
```

Initialise the loop which will break apart the optional argument. The command to print the label is built up in `\@enlab`. `\@enThe` will be used to define `\theenum n`.

```
33 \@enlab}\let\@enThe\@enQmark
```

The `\@enum@` below is never expanded, it is used to detect the end of the token list.

```
34 \@enloop#1\@enum@
```

Issue a warning if we did not find one of the ‘special’ tokens.

```
35 \ifx\@enThe\@enQmark\@warning{The counter will not be printed.%  
36 ^^J\space\@spaces\@spaces\@spaces The label is: \the\@enLab}\fi
```

Define `\labelenum n` and `\theenum n`.

```
37 \expandafter\edef\csname label\@enumctr\endcsname{\the\@enLab}%  
38 \expandafter\let\csname the\@enumctr\endcsname\@enThe
```

Set the counter to 7 so that we get the width of ‘vii’ if roman numbering is in force then set `\leftmargin n` to the width of the label plus `\labelsep`.

```
39 \csname c@\@enumctr\endcsname7  
40 \expandafter\settowidth  
41 \csname leftmargin\romannumeral\@enumdepth\endcsname  
42 {\the\@enLab\hspace{\labelsep}}%
```

Finally call `\@enum@` which is the second half of the original definition.

```
43 \@enum@}
```

`\@enum@` All the list parameters have now been defined, so call `\list`. This is taken straight from the original definition of `\enumerate`.

```
44 \def\@enum@{\list{\csname label\@enumctr\endcsname}%  
45 {\usecounter{\@enumctr}\def\makelabel##1{\hss\llap{##1}}}}
```

```
46 </package>
```